

# FOG 1600 FT™

FOG 1600 FT uses newly designed piping system with electronically controlled electromechanical valve and generates clear burst without excess fog and ensures that only the purest, driest white fog is produced.



This piping design automatically removes remaining fluid from the system, resulting in extended lifespan of the heater unit. Internal electronic fluid level sensor stops operation in low-fluid situations offering complete protection to the heavy-duty and silent running pump and the 100% pure aluminum cast heater.

FOG 1600 FT is the perfect solution for productions needing intensive effects. FOG 1600 FT also caters to the portability needs of the touring and rental markets with custom flight cases available for this fogger.

# Technical Specification

## Description

- Power: AC 230 V/AC 240 V, 50Hz or AC 100 V/AC 120 V, 60 Hz optionally
- Heater: 1,500 WPower Consumption: 1,500 W
- Output: 566 m3/min (20,000 cu.ft./min)
- First Heat-up Time: 10.0 min
- Fluid Consumption Rate: 120 ml/min.
- Tank Capacity: 6 liters
- Low Fluid Indicator: Blue LED
- Weight: 14.5 kg (32.0 lbs)
- Dimensions (mm): L 561 x W 278 x H 186
- Control Feature: Timer, Volume
- Wireless DMX Reciver: CRMX™ from Lumen Radio (Optional)
- Liquid Used: Standard fog / Performance fog / Premium Fog