

# FAZE 1050 FT™

This versatile FAZE 1050 FT™ is the result of an evolution between a fog and a haze machine. The Faze 1050 FT™ has the best features of both technologies without any compromises.



The FAZE emits a fine, dry haze effect which is a perfect compliment for lighting. It is equipped with a range of sophisticated features which include a high precision PCB design; aluminum cast heater, a silent heavy-duty pump and controllable twin fans. Precise fan control is achieved by 3 adjustable levels via onboard DMX. The DMX connection can be via either 3 or 5 pin connector. Silence is golden in some environments, so the FAZE 1050 FT™ is equipped with the quietest pump allowing virtually silent operation, great for noise-sensitive events. A perfect fine particled haze with minimal residue, has a minimal effect on sensitive lighting equipments. FAZE 1050 FT™ has become the machine of choice for stage and studio professionals worldwide.

# Technical Specification

## Description

- Power: AC 230 V/AC 240 V, 50Hz or AC 100 V/AC 120 V/60 Hz optionally
- Heater: 1,000 W
- Output: 99 m<sup>3</sup>/min (3,500 cu.ft/min)
- Fluid Consumption Rate: 45 min/liter (100% Output), 120 min/liter (30% Output)
- First Heat-up Time: 10 min.
- Tank Capacity: 2.4 liter
- Low Fluid Indicator: Blue LED
- Remote Included: Timer Control Module
- Weight: 18.0 kg
- Dimensions (mm): L 635 x W 275 x H 281
- Liquid Used: Standard Fog/Performance Fog/Premium Fog
- DMX Channel Occupied: 2 Channels (one for fog output; one for fan output)

## Approvals

- CE