

ROBIN Forte

Noise Measurement



Date of measurements : 21.5.2021 Temperature / humidity : 20°C / 35 % r.h.

Testing method : EN ISO 9614-1 Acoustics - Determination of **sound power levels** of noise sources
using sound intensity - Part 1: Measurement at discrete points

Testing equipment : Analyzer Brüel & Kjær 2270
Sound intensity probe Brüel & Kjær 3654

1. Sound power levels [dB(A)] - measurement

| [dB(A)] | Settings A)* | Settings B)* | Settings C)* |
|--------------|--------------|--------------|--------------|
| 63 Hz | 3 | 5 | 15 |
| 125 Hz | 17 | 24 | 28 |
| 250 Hz | 30 | 42 | 46 |
| 500 Hz | 37 | 48 | 56 |
| 1 kHz | 36 | 46 | 54 |
| 2 kHz | 36 | 43 | 50 |
| 4 kHz | 26 | 35 | 44 |
| 8 kHz | 17 | 30 | 35 |
| | | | |
| Total | 41 | 52 | 59 |

A)* .. Fans mode: Quiet, 100% dimmer, static position, without effects

B)* .. Fans mode: Auto, 100% dimmer, static position, without effects

C)* .. Fans mode: High, 100% dimmer, static position, without effects

2. Sound pressure levels [dB(A)] – determination

$$L_p = L_w + 10 \log \left(\frac{Q}{4\pi r^2} \right)$$

Q = 2

| [distance (m)] | Settings A)* | Settings B)* | Settings C)* |
|----------------|--------------|--------------|--------------|
| 1 | 33 | 44 | 51 |
| 3 | 24 | 34 | 42 |
| 5 | 19 | 30 | 37 |
| 8 | 15 | 26 | 33 |
| 10 | 13 | 24 | 31 |

A)* .. Fans mode: Quiet, 100% dimmer, static position, without effects

B)* .. Fans mode: Auto, 100% dimmer, static position, without effects

C)* .. Fans mode: High, 100% dimmer, static position, without effects

Test results apply only to the tested specimen.

Copyright © 2021 Robe Lighting s.r.o. – All rights reserved.
All specifications subjects to change without notice

ROBE